

SAFETY DATA SHEET

Creation Date 28-May-2009 Revision Date 14-Feb-2020 Revision Number 2

1. Identification

Product Name tert-Butyl methyl ether

Cat No. : 40477

CAS-No 1634-04-4

Synonyms 2-Methyl-2-methoxy propane; MTBE; Methyl tert-butyl ether

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Alfa Aesar

Thermo Fisher Scientific Chemicals, Inc.

30 Bond Street

Ward Hill, MA 01835-8099

Tel: 800-343-0660 Fax: 800-322-4757 **Email:** tech@alfa.com

www.alfa.com

Emergency Telephone Number

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660.

After normal business hours, call Carechem 24 at (866) 928-0789.

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 2
Skin Corrosion/Irritation Category 2
Specific target organ toxicity (single exposure) Category 3

Target Organs - Lungs.

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor Causes skin irritation May cause respiratory irritation



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Avoid breathing dust/fume/gas/mist/vapors/spray

Response

Get medical attention/advice if you feel unwell

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

Skin

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

Eves

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other hazards

Aspiration hazard if swallowed - can enter lungs and cause damage.

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Methyl tert-butyl ether	1634-04-4	>95

4. First-aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur. If not breathing,

give artificial respiration.

Do NOT induce vomiting. Get medical attention. Ingestion

Most important symptoms and

effects

Notes to Physician

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may

be used to cool closed containers.

No information available **Unsuitable Extinguishing Media**

-28 °C / -18.4 °F **Flash Point**

Method -No information available

224 °C / 435.2 °F **Autoignition Temperature**

Explosion Limits

15.1 vol % Upper Lower 1.6 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO2).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health	Flammability	Instability	Physical hazards
2	3	0	N/A

Accidental release measures

Use personal protective equipment as required. Remove all sources of ignition, Take **Personal Precautions**

precautionary measures against static discharges. Ensure adequate ventilation.

Environmental Precautions Should not be released into the environment. See Section 12 for additional Ecological

Information.

Up

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges.

7. Handling and storage

Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Use only under a chemical fume hood. To avoid ignition of vapors by static electricity discharge, all metal

parts of the equipment must be grounded.

Storage

Flammables area. Keep away from heat, sparks and flame. Keep container tightly closed in a dry and well-ventilated place. May form explosive peroxides on prolonged storage.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Methyl tert-butyl ether	TWA: 50 ppm			TWA: 50 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Engineering Measures Ensure that eyewash stations and safety showers are close to the workstation location.

Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protectionWear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection No protective equipment is needed under normal use conditions.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State Liquid Appearance Colorless

Odor Petroleum distillates
Odor Threshold No information available

pH No information available
Melting Point/Range -110 °C / -166 °F

Boiling Point/Range 54 - 56 °C / 129.2 - 132.8 °F

Flash Point -28 °C / -18.4 °F
Evaporation Rate No information available

Flammability (solid,gas) Not applicable

Flammability or explosive limits

 Upper
 15.1 vol %

 Lower
 1.6 vol %

Vapor Pressure 268 mbar @ 20 °C

Vapor Density 0.2 Specific Gravity 0.740

SolubilitySlightly soluble in waterPartition coefficient; n-octanol/waterNo data availableAutoignition Temperature224 °C / 435.2 °FDecomposition TemperatureNo information available

Viscosity 0.36 mPa.s at 20 °C Molecular Formula C5 H12 O

Molecular Formula C5 H12
Molecular Weight 88.15

10. Stability and reactivity

Revision Date 14-Feb-2020

tert-Butyl methyl ether

Reactive Hazard None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials Strong oxidizing agents

Hazardous Decomposition Products Carbon monoxide (CO₂), Carbon dioxide (CO₂)

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

Toxicological information

Acute Toxicity

Product Information

Component Information

Component LD50 Oral		LD50 Dermal	LC50 Inhalation	
	Methyl tert-butyl ether	LD50 = 2963 mg/kg (Rat)	LD50 = 10000 mg/kg (Rabbit)	LC50 = 85 mg/L (Rat) 4 h

Toxicologically Synergistic

Products

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes and skin

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Limited evidence of a carcinogenic effect.

	Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
	Methyl tert-butyl ether	1634-04-4	Not listed	Not listed	A3	Not listed	A3
ACGIH: (American Conference of Governmental Industrial				al A1 - Known	Human Carcinogen	-	

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mutagenic effects have occurred in experimental animals. **Mutagenic Effects**

Reproductive Effects No information available. **Developmental Effects** No information available. **Teratogenicity** No information available.

STOT - single exposure Lungs STOT - repeated exposure None known

No information available **Aspiration hazard**

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting

Endocrine Disruptor Information

Component EU - Endocrine Disrupters Candidate List		EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information	
	Methyl tert-butyl ether	Group III Chemical	Not applicable	Not applicable

tert-Butyl methyl ether Revision Date 14-Feb-2020

Other Adverse Effects

Tumorigenic effects have been reported in experimental animals.

12. Ecological information

Ecotoxicity

Do not empty into drains. .

Comp	onent	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Methyl tert-	butyl ether	800 mg/L EC50 > 72 h	887 mg/L LC50 96 h	EC50 = 11.4 mg/L 30 min	EC50: = 542 mg/L, 48h
		184 mg/L EC50 = 96 h	100 mg/L LC50 96 h	EC50 = 8.23 mg/L 5 min	(Daphnia magna)
			929 mg/L LC50 96 h	EC50 = 9.67 mg/L 15 min	
			672 mg/L LC50 96 h	_	

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
Methyl tert-butyl ether	1.06

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN2398

Proper Shipping Name METHYL tert-BUTYL ETHER

Hazard Class 3
Packing Group ||

TDG

UN-No UN2398

Proper Shipping Name METHYL tert-BUTYL ETHER

Hazard Class 3
Packing Group ||

<u>IATA</u>

UN-No UN2398

Proper Shipping Name METHYL tert-BUTYL ETHER

Hazard Class 3 Packing Group II

IMDG/IMO

UN-No UN2398

Proper Shipping Name METHYL tert-BUTYL ETHER

Hazard Class 3
Packing Group ||

15. Regulatory information

United States of America Inventory

Component	CAS-No	TSCA	TSCA Inventory notification - Active/Inactive	TSCA - EPA Regulatory Flags
Methyl tert-butyl ether	1634-04-4	X	ACTIVE	-

Legend:

TSCA - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

tert-Butyl methyl ether

TSCA 12(b) - Notices of Export

Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Australia (AICS), China (IECSC), Korea (ECL).

Component	CAS-No	DSL	NDSL	EINECS	PICCS	ENCS	AICS	IECSC	KECL
Methyl tert-butyl ether	1634-04-4	X	-	216-653-1	X	X	Χ	Х	KE-23648

U.S. Federal Regulations

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Methyl tert-butyl ether	1634-04-4	>95	1.0

SARA 311/312 Hazard Categories

See section 2 for more information

CWA (Clean Water Act)

Not applicable

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl tert-butyl ether	X		-

OSHA - Occupational Safety and

Health Administration

Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs	
Methyl tert-butyl ether	1000 lb	=	

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Methyl tert-butyl ether	X	Х	X	X	-

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

16. Other information

Prepared By Health, Safety and Environmental Department

Email: tech@alfa.com

www.alfa.com

Revision Date 14-Feb-2020

 Creation Date
 28-May-2009

 Revision Date
 14-Feb-2020

 Print Date
 14-Feb-2020

Revision Summary SDS authoring systems update, replaces ChemGes SDS No. 1634-04-4/4.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS