

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

SECTION 1. IDENTIFICATION

Product name : CLEAR COAT

Product code : 08930191

Manufacturer or supplier's details

Company name of supplier : Wurth USA Inc.

Address : 93 Grant St.
Ramsey, NJ 07446

Telephone : (201) 825-2710

Telefax : (201) 825-1643

Emergency telephone : +1 800 255 3924

E-mail address : prodsafe@wuerth.com

Recommended use of the chemical and restrictions on use

Recommended use : Paints

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable aerosols : Category 1

Gases under pressure : Liquefied gas

Eye irritation : Category 2A

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 3
- single exposure

Specific target organ toxicity : Category 2 (Central nervous system)
- repeated exposure

Simple Asphyxiant

GHS label elements

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

Hazard pictograms

:



Signal Word

:

Danger

Hazard Statements

:

H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs (Central nervous system) through prolonged or repeated exposure.
May displace oxygen and cause rapid suffocation.

Precautionary Statements

:

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, sparks, open flame and hot surfaces. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P260 Do not breathe spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical attention.
P337 + P313 If eye irritation persists: Get medical attention.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version 6.1 Revision Date: 06/17/2024 SDS Number: 10692074-00009 Date of last issue: 05/15/2023
Date of first issue: 03/02/2015

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Acetone	67-64-1	$\geq 30 - < 50$
Propane	74-98-6	$\geq 10 - < 20$
n-Butyl acetate	123-86-4	$\geq 10 - < 20$
Butanone	78-93-3	$\geq 10 - < 20$
Isobutane	75-28-5	$\geq 5 - < 10$
Toluene	108-88-3	$\geq 5 - < 10$
2-Methoxy-1-methylethyl acetate	108-65-6	$\geq 1 - < 5$
Diacetone alcohol	123-42-2	$\geq 1 - < 5$

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention immediately.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Gas reduces oxygen available for breathing.
Prolonged or repeated contact may dry skin and cause irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of damaging the unborn child.
May cause damage to organs through prolonged or repeated exposure.
May displace oxygen and cause rapid suffocation.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Remove all sources of ignition.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
Do not breathe spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.

Conditions for safe storage : Store locked up.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version
6.1

Revision Date:
06/17/2024

SDS Number:
10692074-00009

Date of last issue: 05/15/2023
Date of first issue: 03/02/2015

Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m ³	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m ³	OSHA Z-1
Propane	74-98-6	TWA	1,000 ppm 1,800 mg/m ³	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m ³	OSHA Z-1
n-Butyl acetate	123-86-4	TWA	150 ppm 710 mg/m ³	NIOSH REL
		ST	200 ppm 950 mg/m ³	NIOSH REL
		TWA	150 ppm 710 mg/m ³	OSHA Z-1
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Butanone	78-93-3	TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
		TWA	200 ppm 590 mg/m ³	NIOSH REL
		ST	300 ppm 885 mg/m ³	NIOSH REL
		TWA	200 ppm 590 mg/m ³	OSHA Z-1
Isobutane	75-28-5	TWA	800 ppm 1,900 mg/m ³	NIOSH REL
		STEL	1,000 ppm	ACGIH
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m ³	NIOSH REL
		ST	150 ppm 560 mg/m ³	NIOSH REL
		TWA	200 ppm	OSHA Z-2

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version 6.1 Revision Date: 06/17/2024 SDS Number: 10692074-00009 Date of last issue: 05/15/2023
Date of first issue: 03/02/2015

		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm (10 minutes)	OSHA Z-2
2-Methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm	US WEEL
Diacetone alcohol	123-42-2	TWA	50 ppm	ACGIH
		TWA	50 ppm 240 mg/m ³	NIOSH REL
		TWA	50 ppm 240 mg/m ³	OSHA Z-1

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g creatinine	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust venti-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

lation.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

Propellant	:	Isobutane, Propane
Color	:	clear
Odor	:	fruity
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	135 - 334 °F / 57 - 168 °C
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	15.1 %(V)
Lower explosion limit / Lower flammability limit	:	1.0 %(V)
Vapor pressure	:	3,800 - 4,500 hPa (68 °F / 20 °C)
Relative vapor density	:	> 1
Density	:	0.73 - 0.77 g/cm ³
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	522 - 896 °F / 272 - 480 °C
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics
Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.
Vapors may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 105.81 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Components:

Acetone:

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): 7,426 mg/kg

Propane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm
Exposure time: 15 min
Test atmosphere: gas

n-Butyl acetate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 21.1 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Butanone:

Acute oral toxicity : LD50 (Rat): > 2,000 - 5,000 mg/kg
Remarks: Based on data from similar materials
Acute inhalation toxicity : LC50 (Rat): > 25.5 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 436
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Isobutane:

Acute inhalation toxicity : LC50 (Mouse): 260200 ppm
Exposure time: 4 h
Test atmosphere: gas

Toluene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): 28.1 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

2-Methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 (Rat, female): 5,155 mg/kg

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

Acute inhalation toxicity : LC50 (Rat): > 9.34 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Diacetone alcohol:

Acute oral toxicity : LD50 (Rat): 3,002 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 7.6 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Acetone:

Assessment : Repeated exposure may cause skin dryness or cracking.

n-Butyl acetate:

Species : Rabbit
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Butanone:

Assessment : Repeated exposure may cause skin dryness or cracking.

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Toluene:

Species : Rabbit
Method : Directive 67/548/EEC, Annex V, B.4.
Result : Skin irritation

2-Methoxy-1-methylethyl acetate:

Species : Rabbit
Result : No skin irritation

Diacetone alcohol:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

Species	:	Rabbit
Result	:	No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Acetone:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days
Method	:	OECD Test Guideline 405

n-Butyl acetate:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

Butanone:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days
Method	:	OECD Test Guideline 405

Toluene:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

2-Methoxy-1-methylethyl acetate:

Species	:	Rabbit
Result	:	No eye irritation

Diacetone alcohol:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 7 days
Method	:	OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Acetone:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

Species : Guinea pig
Result : negative

n-Butyl acetate:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Butanone:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Toluene:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : Directive 67/548/EEC, Annex V, B.6.
Result : negative

2-Methoxy-1-methylethyl acetate:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Diacetone alcohol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Acetone:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version 6.1	Revision Date: 06/17/2024	SDS Number: 10692074-00009	Date of last issue: 05/15/2023 Date of first issue: 03/02/2015
----------------	------------------------------	-------------------------------	---

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

n-Butyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Butanone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Test Type: Saccharomyces cerevisiae, gene mutation assay (in vitro)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Isobutane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Toluene:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Intraperitoneal injection
Result: negative

Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: inhalation (vapor)
Method: OECD Test Guideline 478
Result: negative

2-Methoxy-1-methylethyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Diacetone alcohol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

Carcinogenicity

Not classified based on available information.

Components:

Acetone:

Species	:	Mouse
Application Route	:	Skin contact
Exposure time	:	424 days
Result	:	negative

Toluene:

Species	:	Rat
Application Route	:	inhalation (vapor)
Exposure time	:	103 weeks
Result	:	negative

Species	:	Mouse
Application Route	:	Skin contact
Exposure time	:	24 Months
Result	:	negative

2-Methoxy-1-methylethyl acetate:

Species	:	Rat
Application Route	:	inhalation (vapor)
Exposure time	:	2 Years
Method	:	OECD Test Guideline 453
Result	:	negative
Remarks	:	Based on data from similar materials

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

Acetone:

Effects on fertility	:	Test Type: One-generation reproduction toxicity study Species: Rat Application Route: Ingestion Result: negative
----------------------	---	---

Effects on fetal development	:	Test Type: Embryo-fetal development
------------------------------	---	-------------------------------------

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

Species: Rat
Application Route: inhalation (vapor)
Result: negative

Propane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

n-Butyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Butanone:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 414
Result: negative

Isobutane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 422
Result: negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Toluene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

2-Methoxy-1-methylethyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Diacetone alcohol:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

STOT-single exposure

May cause drowsiness or dizziness.
May displace oxygen and cause rapid suffocation.

Components:

Acetone:

Assessment : May cause drowsiness or dizziness.

Propane:

Assessment : May cause drowsiness or dizziness.

n-Butyl acetate:

Assessment : May cause drowsiness or dizziness.

Butanone:

Assessment : May cause drowsiness or dizziness.

Isobutane:

Assessment : May cause drowsiness or dizziness.

Toluene:

Assessment : May cause drowsiness or dizziness.

2-Methoxy-1-methylethyl acetate:

Assessment : May cause drowsiness or dizziness.

Diacetone alcohol:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

Components:

Toluene:

Routes of exposure : Inhalation
Target Organs : Central nervous system
Assessment : May cause damage to organs through prolonged or repeated exposure.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

Repeated dose toxicity

Components:

Acetone:

Species	: Rat
NOAEL	: 900 mg/kg
LOAEL	: 1,700 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days

Species	: Rat
NOAEL	: 45 mg/l
Application Route	: inhalation (vapor)
Exposure time	: 8 Weeks

Propane:

Species	: Rat
NOAEL	: 7.214 mg/l
Application Route	: inhalation (gas)
Exposure time	: 6 Weeks
Method	: OECD Test Guideline 422

n-Butyl acetate:

Species	: Rat
NOAEL	: 2.4 mg/l
Application Route	: inhalation (vapor)
Exposure time	: 90 Days

Butanone:

Species	: Rat
NOAEL	: 14.84 mg/l
Application Route	: inhalation (vapor)
Exposure time	: 90 Days
Method	: OECD Test Guideline 413

Isobutane:

Species	: Rat
NOAEL	: 9000 ppm
Application Route	: inhalation (gas)
Exposure time	: 6 Weeks
Method	: OECD Test Guideline 422

Toluene:

Species	: Rat
LOAEL	: 1.875 mg/l
Application Route	: inhalation (vapor)
Exposure time	: 6 Months

Species	: Rat
---------	-------

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

NOAEL : 625 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

2-Methoxy-1-methylethyl acetate:

Species : Rat
NOAEL : $\geq 1,000$ mg/kg
Application Route : Ingestion
Exposure time : 41 - 45 Days
Method : OECD Test Guideline 422

Species : Rat
NOAEL : > 1 mg/l
Application Route : inhalation (vapor)
Exposure time : 2 y
Method : OECD Test Guideline 453
Remarks : Based on data from similar materials

Species : Rabbit
NOAEL : > 200 mg/kg
Application Route : Skin contact
Exposure time : 90 Days
Remarks : Based on data from similar materials

Diacetone alcohol:

Species : Rat
NOAEL : ≥ 600 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks
Method : OECD Test Guideline 408

Species : Rat
NOAEL : ≥ 4.685 mg/l
Application Route : inhalation (vapor)
Exposure time : 6 Weeks

Aspiration toxicity

Not classified based on available information.

Components:

Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

Butanone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

Toluene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Experience with human exposure

Components:

Toluene:

Inhalation : Target Organs: Central nervous system
Symptoms: Neurological disorders

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Acetone:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia pulex (Water flea)): 8,800 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000
plants mg/l
Exposure time: 96 h

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): >= 79 mg/l
aquatic invertebrates (Chron- Exposure time: 21 d
ic toxicity) Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: 61,150 mg/l
Exposure time: 30 min
Method: ISO 8192

n-Butyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia sp. (Water flea)): 44 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): 397
plants mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 196

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 23.2 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

Butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,993 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 308 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 2,029 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 1,240 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

Toluene:

Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 5.5 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Skeletonema costatum (marine diatom)): 10 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus kisutch (coho salmon)): 1.39 mg/l
Exposure time: 40 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): 0.74 mg/l
Exposure time: 7 d

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 84 mg/l
Exposure time: 24 h

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

2-Methoxy-1-methylethyl acetate:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 - 180 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 500 mg/l
Exposure time: 48 h
Method: Directive 67/548/EEC, Annex V, C.2.
- Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): > 1,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201
- NOEC (Raphidocelis subcapitata (freshwater green alga)): >= 1,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 100 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
- Toxicity to microorganisms : EC10 (activated sludge): > 1,000 mg/l
Exposure time: 30 min

Diacetone alcohol:

- Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): > 1,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- NOEC (Raphidocelis subcapitata (freshwater green alga)): > 1,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 100 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
- Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

Persistence and degradability

Components:

Acetone:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 91 %
Exposure time: 28 d

Propane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

n-Butyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Butanone:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 98 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Isobutane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Toluene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 20 d

2-Methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Diacetone alcohol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 98.51 %

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

Exposure time: 28 d

Bioaccumulative potential

Components:

Acetone:

Partition coefficient: n-octanol/water : log Pow: -0.27 - -0.23

n-Butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2.3

Butanone:

Partition coefficient: n-octanol/water : log Pow: 0.3

Isobutane:

Partition coefficient: n-octanol/water : log Pow: 2.8

Toluene:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 90

Partition coefficient: n-octanol/water : log Pow: 2.73

2-Methoxy-1-methylethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1.2

Diacetone alcohol:

Partition coefficient: n-octanol/water : log Pow: -0.09
Remarks: Calculation

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1950
Proper shipping name : Aerosols

Class : 2.1
Packing group : Not assigned by regulation

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version 6.1 Revision Date: 06/17/2024 SDS Number: 10692074-00009 Date of last issue: 05/15/2023
Date of first issue: 03/02/2015

Labels : FLAMMABLE GAS
ERG Code : 126
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Toluene	108-88-3	1000	12500
Acetone	67-64-1	5000	13888
n-Butyl acetate	123-86-4	5000	35714

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Gases under pressure
Simple Asphyxiant
Serious eye damage or eye irritation
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Toluene 108-88-3 $\geq 5 - < 10 \%$

Volatile organic compounds (VOC) content : 40 CFR Part 59 National VOC Emission Standards For Aerosol Coatings, Subpart E
VOC content: 50 - 60 % / < 450 g/l
Category: 0.85 (CCP): Clear Coatings

US State Regulations

Pennsylvania Right To Know

Acetone	67-64-1
Propane	74-98-6
n-Butyl acetate	123-86-4
Acrylic Resin	Not Assigned
Butanone	78-93-3
Isobutane	75-28-5
Toluene	108-88-3
2-Methoxy-1-methylethyl acetate	108-65-6

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

Diacetone alcohol

123-42-2

California Prop. 65

WARNING: This product can expose you to chemicals including Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Acetone	67-64-1
n-Butyl acetate	123-86-4
Butanone	78-93-3
Toluene	108-88-3
Diacetone alcohol	123-42-2

California Permissible Exposure Limits for Chemical Contaminants

Acetone	67-64-1
Propane	74-98-6
n-Butyl acetate	123-86-4
Butanone	78-93-3
Toluene	108-88-3
2-Methoxy-1-methylethyl acetate	108-65-6
Diacetone alcohol	123-42-2

The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT


Version
6.1

Revision Date:
06/17/2024

SDS Number:
10692074-00009

Date of last issue: 05/15/2023
Date of first issue: 03/02/2015

NFPA 704:



HMIS® IV:

HEALTH	*	2
FLAMMABILITY		4
PHYSICAL HAZARD		3

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	: USA. Occupational Exposure Limits (OSHA) - Table Z-2
US WEEL	: USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-2 / TWA	: 8-hour time weighted average
OSHA Z-2 / CEIL	: Acceptable ceiling concentration
OSHA Z-2 / Peak	: Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift
US WEEL / TWA	: 8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



CLEAR COAT

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2023
6.1	06/17/2024	10692074-00009	Date of first issue: 03/02/2015

tion; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 06/17/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8